


High sparkle control surface-mounted round spot. Suitable for all types of general lighting applications. Integrated lighting solution with LED-On XL Module. Compatible with all AR111 lamp options. Tool-free module or lamp installation. Various frame and body color options to match the design. Easy locking mechanism for body mounting and maintenance. Maintenance-free engineering plastic body. Long-lasting LED product with aluminum outer body. Long-lasting and lightweight design. No special tools required for ceiling mounting.



- Outer Diameter - \varnothing 185mm
- Height - 125mm
- COB (2700K, 3000K, 4000K) LED Options
- SMD (3000K, 4000K) LED Options
- Flame-retardant ABS Body
-

Description	Power (W)	Lumen (lm)	CCT (Kelvin)	CRI	Current (mA) /Voltage (V)	Code
Pulse XL COB RS Spot	15 W	1800	2700 K	80+	350 mA	ITX001.015.827.XXX.AA.Y
Pulse XL COB RS Spot	20 W	2300	2700 K	80+	500 mA	ITX001.020.827.XXX.AA.Y
Pulse XL COB RS Spot	15 W	1900	3000 K	80+	350 mA	ITX001.015.830.XXX.AA.Y
Pulse XL COB RS Spot	20 W	2400	3000 K	80+	500 mA	ITX001.020.830.XXX.AA.Y
Pulse XL COB RS Spot	15 W	1970	4000 K	80+	350 mA	ITX001.015.840.XXX.AA.Y
Pulse XL COB RS Spot	20 W	2500	4000 K	80+	500 mA	ITX001.020.840.XXX.AA.Y
Pulse XL SMD RS Spot	15 W	2530	3000 K	80+	350 mA	ITX002.015.830.XXX.AA.Y
Pulse XL SMD RS Spot	20 W	3560	3000 K	80+	500 mA	ITX002.020.830.XXX.AA.Y
Pulse XL SMD RS Spot	15 W	2590	4000 K	80+	350 mA	ITX002.015.840.XXX.AA.Y
Pulse XL SMD RS Spot	20 W	3650	4000 K	80+	500 mA	ITX002.020.840.XXX.AA.Y

