





High sparkle control frameless (trimless) spot. Suitable for all types of general lighting applications. Integrated lighting solution with LED-On XL Module. Compatible with all AR111 lamp options. Tool-free module or lamp installation. Various frame and body color options to match the design. Mounting brackets suitable for all types of plasterboard thicknesses. Maintenance-free engineering plastic body. Long-lasting and lightweight design. Easy installation and maintenance with trimless special locking mechanism.

- Outer Diameter - Ø255mm
- Hole Diameter - Ø145mm
- **COB** (2700K, 3000K, 4000K) Led Options
- **SMD** (3000K, 4000K) Led Options
- Flame-retardant ABS Body Material



Description	Power (W)	Lumen (lm)	CCT (Kelvin)	CRI	Current (mA) /Voltage (V)	Code
Pulse XL COB RS Spot	15 W	1800	2700 K	80+	350 mA	IGX004.015.827.XXX.AA.Y
Pulse XL COB RS Spot	20 W	2300	2700 K	80+	500 mA	IGX004.020.827.XXX.AA.Y
Pulse XL COB RS Spot	15 W	1900	3000 K	80+	350 mA	IGX004.015.830.XXX.AA.Y
Pulse XL COB RS Spot	20 W	2400	3000 K	80+	500 mA	IGX004.020.830.XXX.AA.Y
Pulse XL COB RS Spot	15 W	1970	4000 K	80+	350 mA	IGX004.015.840.XXX.AA.Y
Pulse XL COB RS Spot	20 W	2500	4000 K	80+	500 mA	IGX004.020.840.XXX.AA.Y
Pulse XL SMD RS Spot	15 W	2530	3000 K	80+	350 mA	IGX005.015.830.XXX.AA.Y
Pulse XL SMD RS Spot	20 W	3560	3000 K	80+	500 mA	IGX005.020.830.XXX.AA.Y
Pulse XL SMD RS Spot	15 W	2590	4000 K	80+	350 mA	IGX005.015.840.XXX.AA.Y
Pulse XL SMD RS Spot	20 W	3650	4000 K	80+	500 mA	IGX005.020.840.XXX.AA.Y

